

EP-08/EP-15/EP-25 Elevating Prefeeder

Designed for Floor Level Parts Loading

Product Overview:

Hoppmann's standard EP-08/08 elevating prefeeder is designed to handle a variety of medium-sized, light weight parts. Its eight (8) cubic foot capacity hopper delivers product at an average belt speed of 32 feet per minute. The cleated elevator belt has a nominal cleat height of 2.00" and a cleat pitch of 6.00" allowing for maximum product loading. A heavy duty variable speed motor helps to ensure proper product metering.

Product Specifications:

	ANSI	Metric
A. Overall Width	42"	1067mm
B. Overall Length	63"	1600mm
C. Lower Chassis Footprint	63.10"	1603mm
D. Dump Height (Adjustable)	42"-53"	1067-1346mm
E. Hopper Load Height (8 cu. ft.)	34"	864mm
Hopper Load Height (15 cu. ft.)	42"	1067mm
Hopper Load Height (25 cu. ft.)	50"	1270mm
F. Belt Width	8"	203mm

Standard Models:

Part Number	EP0808XDSA	EP0808XASA
Motor Style	DC	AC
Motor Voltage	130V	230/460V
Horsepower	1/4 hp	1/4 hp
Total Equipment Weight	720 lbs.	720 lbs.



Standard Features:

- All stainless steel construction
- Belting is FDA/USDA approved white 1-ply solid woven polyester fabric with 1/16" thick white PVC coating and PVC cleats
- Hopper cleanout door
- One piece formed hopper (EP-08)

Available Options:

- Elevator extensions
- Continuous welded hopper seams (EP-15 and EP-25)
- Elevator/hopper covers
- Washdown motor
- Mounted controller
- Casters
- Hopper extensions for 15 and 25 cubic foot capacities
- Mechanical style level sensor (proximity sensor not included)
- Modular plastic chain upgrade
- Pneumatic part agitator (hopper)

